

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: 11013VH

**Model Number:** XPB308-103IN6TL21

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 30A, 120/208V WYE, 8.6kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Basic Standard, 30A, 120/208V WYE, 8.6kW, Vertical, (24) IEC C13, (6) IEC C19, 10ft power cord with L21-30P, Black Powder Coat.

### Plug Form:



L21-30P

### Receptacle:



IEC C13  
(Quantity: 24)



IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |                      |
|------------------------------|----------------------|
| Quantity Of Inputs           | 1                    |
| Voltage                      | 100-120/200-240V WYE |
| Current                      | 30A x 3 Phase WYE    |
| VA per Input (Load Capacity) | 8.6kW (208V)         |
| Frequency                    | 50/60Hz              |

|  |   |
|--|---|
| <b>Over Current Protection</b>                               | (3) 20A Double Pole Magnetic Breakers   |
| <b>Switch</b>  | Breaker/Switch Combination  |
| <b>Power Cable Wire Gauge</b>                                | 10/5  |
| <b>Power Cable Length</b>                                    | 10ft  |
| <b>Plug Type</b>   | NEMA L21-30P Twistlock  |
| <b>Combined Total Receptacle/Socket Quantity</b>             | 30  |
| <b>Receptacle/Socket Type #1</b>                             | IEC C13   |
| - Quantity on Face   | 24  |
| - Quantity per Breaker and Phase Combination                 | 8   |
| - Style  | Banks of 4  |
| - Maximum Output per Receptacle/Socket                       | 15A per receptacle bank   |
| - Voltage per Receptacle/Socket                              | 208V  |
| <b>Receptacle/Socket Type #2</b>                             | IEC C19   |
| - Quantity on Face   | 6   |
| - Quantity per Breaker and Phase Combination                 | 2   |
| - Style  | Individual  |
| - Maximum Output per Receptacle/Socket                       | 20A   |
| - Voltage per Receptacle/Socket                              | 208V  |
| <b>Continuous Operating Temperature Range</b>                | 10-45C / 50-113F  |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black   |
| <b>Configuration</b>   | 66in / 1683mm Vertical Rackmount  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in   |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant  |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 60950  |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2.0in x 2.0in   |
| <b>Doghouse (D)</b>  | 1.44in  |
| <b>Shipped Weight</b>  | 17lbs (7.71kg)  |