

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: 11027VH

**Model Number:** VRELN080-103I44TL6

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 30A, 208V, 4.9kW

**Physical Configuration:** 17in / 432mm, Horizontal/Vertical

**Product Summary:** rPDU, Basic Standard, 30A, 208V, 4.9kW, Horizontal/Vertical, (4) IEC C13, (4) IEC C19, 10ft power cord with L6-30P, Black Powder Coat.

### Plug Form:



L6-30P

### Receptacle:



IEC C13  
(Quantity: 4)



IEC C19  
(Quantity: 4)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	30A

<b>VA per Input (Load Capacity)</b>	4.9kW (208V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(4) 15A Thermal Breakers
<b>Switch</b>	No
<b>Power Cable Wire Gauge</b>	10/3
<b>Power Cable Length</b>	10ft
<b>Plug Type</b>	NEMA L6-30P Twistlock
<b>Combined Total Receptacle/Socket Quantity</b>	8
<b>Receptacle/Socket Type #1</b>	IEC C13
- Quantity on Face	4
- Quantity per Breaker Pair	2
- Style	Banks of 2
- Maximum Output per Receptacle/Socket	15A per receptacle bank
- Voltage per Receptacle/Socket	208V
<b>Receptacle/Socket Type #2</b>	IEC C19
- Quantity on Face	4
- Quantity per Breaker Pair	2
- Style	Individual
- Maximum Output per Receptacle/Socket	20A
- Voltage per Receptacle/Socket	208V
<b>Continuous Operating Temperature Range</b>	10-45C / 50-113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	17in / 432mm Vertical/Horizontal Rackmount
<b>19in Panel Mount Brackets</b>	Yes
<b>SLB-4 Brackets</b>	Yes
<b>Country of Origin</b>	USA, TAA Compliant and Buy American Act COTS Compliant
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	UL & c-UL Listed Accessory 1950
<b>Chassis Dimensions (LxWxD)</b>	17.0in x 1.72in x 1.85in
<b>Shipped Weight</b>	7lbs (3.18kg)