

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: 15654VH

**Model Number:** XPRA120-103D20TL6

**Category:** Metered

**Sub Category:** Standard

**Power Configuration:** 30A, 208V, 4.9kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Metered Standard, 30A, 208V, 4.9kW, Horizontal, (12) NEMA 6-20R, 10ft power cord with L6-30P, Black Powder Coat.

### Monitoring:

Current - Local

Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



L6-30P

### Receptacle:



NEMA 6-20R  
(Quantity: 12)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

<b>Monitoring</b>	Current - Local
	Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
<b>Monitoring Level 1</b>	Aggregate - Total Unit Monitoring
<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	200-240V
<b>Current</b>	30A
<b>VA per Input (Load Capacity)</b>	4.9kW (208V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(2) 20A Double Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	10/3
<b>Power Cable Length</b>	10ft
<b>Plug Type</b>	NEMA L6-30P Twistlock
<b>Receptacle/Socket Type #1</b>	NEMA 6-20R
<b>- Quantity on Face</b>	2
<b>- Quantity on Rear</b>	10
<b>- Quantity per Breaker</b>	6
<b>- Style</b>	Duplex
<b>- Maximum Output per Receptacle/Socket</b>	20A
<b>- Voltage per Receptacle/Socket</b>	208V
<b>Continuous Operating Temperature Range</b>	10-45C / 50-113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	19in / 483mm Horizontal Rackmount
<b>Adjustable Mount Brackets</b>	Yes
<b>Country of Origin</b>	USA, TAA Compliant and Buy American Act COTS Compliant
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	UL & c-UL Listed 60950
<b>Chassis Dimensions (HxWxD)</b>	1.72in x 17in x 6.50in
<b>Shipped Weight</b>	8lbs (3.63kg)