

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



### Part #: 38563

**Model Number:** VRELCN080-103C13TL6

**Category:** Metered

**Sub Category:** Standard

**Power Configuration:** 30A, 208V, 4.9kW

**Physical Configuration:** 17in / 432mm, Horizontal/Vertical

### Product Summary:

rPDU, Metered Standard, 30A, 208V, 4.9kW, Horizontal/Vertical, (8) IEC C13, 10ft power cord with L6-30P, Black Powder Coat.

### Monitoring:

Power - Local (A, V, W, PF)

Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



L6-30P

### Receptacle:



IEC C13  
(Quantity: 8)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|  |   |
|--|---|
| Monitoring                             | Power - Local (A, V, W, PF)<br>Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input |
| Monitoring Level 1                     | Aggregate - Total Unit Monitoring   |
| Quantity Of Inputs                     | 1   |
| Voltage                                | 200-240V  |
| Current                                | 30A   |
| VA per Input (Load Capacity)           | 4.9kW (208V)  |
| Frequency                              | 50/60Hz   |
| Over Current Protection                | (4) 15A Thermal Breakers  |
| Switch                                 | No  |
| Power Cable Wire Gauge                 | 10/3  |
| Power Cable Length                     | 10ft  |
| Plug Type                              | NEMA L6-30P Twistlock   |
| Receptacle/Socket Type #1              | IEC C13   |
| - Quantity on Face                     | 8   |
| - Quantity per Breaker Pair            | 4   |
| - Style                                | Banks of 4  |
| - Maximum Output per Receptacle/Socket | 15A per receptacle bank   |
| - Voltage per Receptacle/Socket        | 208V  |
| Continuous Operating Temperature Range | 10-45C / 50-113F  |
| Heavy Steel - Powder Coat Finish       | Black   |
| Configuration                          | 17in / 432mm Vertical/Horizontal Rackmount  |
| 19in Panel Mount Brackets              | Yes   |
| SLB-4 Brackets                         | Yes   |
| Country of Origin                      | USA, TAA Compliant and Buy American Act COTS Compliant  |
| Product Warranty                       | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years             |
| Certification/Agency Approvals         | RoHS Compliant  |
| Certification/Agency Approvals         | UL & c-UL Listed Accessory 1950   |
| Chassis Dimensions (LxWxD)             | 17.00in x 1.72in x 1.61in   |
| Shipped Weight                         | 6lbs (2.72kg)   |