

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.

□

Part #: 38664

Model Number: 2VHVLN162-102C13TL6

Category: Basic

Sub Category: Standard

Power Configuration: 20A, 208V, 3.3kW

Physical Configuration: 2U 19in / 483mm, Horizontal

Product Summary:

rPDU, Basic Standard, 20A, 208V, 3.3kW, Horizontal, (16) IEC C13, 10ft power cord with L6-20P, Black Powder Coat.

Plug Form:



L6-20P

Receptacle:



IEC C13
(Quantity: 16)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|------------------------------|--------------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 20A |
| VA per Input (Load Capacity) | 3.3kW (208V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |

| | |
|--|-----------------------------------|
| Switch | No |
| Power Cable Wire Gauge | 12/3 |
| Power Cable Length | 10ft |
| Plug Type | NEMA L6-20P Twistlock |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 16 |
| - Style | Banks of 4 |
| - Maximum Output per Receptacle/Socket | 15A per receptacle bank |
| - Voltage per Receptacle/Socket | 208V |
| Continuous Operating Temperature Range | 10-45C / 50-113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 19in / 483mm Horizontal Rackmount |
| Flush Mount | Yes |
| TAA Compliant and BAA / COTS Compliant | Yes, when County of Origin is USA |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | UL & c-UL Listed 60950 |
| Chassis Dimensions (HxWxD) | 3.45in x 17in x 1.61in |
| Shipped Weight | 8lbs (3.63kg) |