

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EPOG01A0

Model Number: VCOAEDOC08N0DXX

Category: Basic

Sub Category: Standard

Power Configuration: 10A, 230V, 2.3kW


Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU - Basic Standard, 10A, 230V, 2.3kW, 1U Horizontal, (8) German Schuko, 3m power cord with C14, Black Powder Coat

Plug Form:

C14

Receptacle:German Schuko
(Quantity: 8)**Product Specification and Options****System Features**

Quantity Of Inputs	1
Voltage	230V
Current	10A
VA per Input (Load Capacity)	2.3kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.5mm ² H05VVF
Power Cable Length	3m
Plug Type	IEC60320 C14 (corded)
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	8
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U, Horizontal Rackmount
Adjustable Mount Brackets	No
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	FCC Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Chassis Dimensions (HxWxD)	44.4mm x 435mm x 44mm
Shipping Weight	3.5 lbs (1.55 kg)