

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G81A0

Model Number: VC0AFD0A09N0DXX

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU - Basic Standard, 16A, 230V, 3.6kW, 1U Horizontal, (9) Manual locking IEC C13, 3m power cord with German Schuko, Black Powder Coat

Plug Form:



Schuko

Receptacle:



IEC C13
(Quantity: 9)

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm ² H07RN-F
Power Cable Length	3m

Plug Type	16A Schuko
Receptacle/Socket Type #1	Manual Locking IEC C13
- Quantity on Face	9
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (HxWxD)	44.4mm x 435mm x 44mm
Shipping Weight	3.5 lbs (1.55 kg)