

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



## Part #: EP0G81A1

**Model Number:** VC0AFD0C08N0DXX

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU - Basic Standard, 16A, 230V, 3.6kW, 1U Horizontal, (8) German Schuko, 3m power cord with German Schuko, Black Powder Coat

### Plug Form:



Schuko

### Receptacle:



German Schuko  
(Quantity: 8)

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm <sup>2</sup> H07RN-F
Power Cable Length	10ft / 3m

Plug Type	16A Schuko
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	8
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U, Horizontal Rackmount
Adjustable Mount Brackets	No
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (HxWxD)	44.4mm x 435mm x 44mm
Shipping Weight	5.5lbs (2.5kg)