## Vertiv<sup>™</sup> PowerIT rPDU

# VERTIV.

## **OVERVIEW**

The Vertiv Geist FSC, Facility Side Cable, features a universal connector designed to mate with the Universal Input on the Vertiv Geist UPDU, Universal Power Distribution Unit. The FSC is available in common worldwide AC power specs ranging from 16A to 60A, 120V to 415V with single and three phase power configurations. Select the detachable Vertiv Geist FSC specific to the local power configuration to power the UPDU. (UPDU sold separately)

#### **Benefits**

- The flexibility offered by the UPDU and FSC enable any rack architecture to be installed in any data center around the world, regardless of the power infrastructure already in place.
- The FSC enables users to utilize a single UPDU model with various input power configurations to simplify global IT infrastructure deployments, inventory management and enable rapid deployments worldwide.
- Increase or decrease UPDU power capacity by changing the FSC to adapt to fluctuating equipment power needs.
- Every unit is 100% tested for reliability and functionality to ensure units function as designed.



## Part #: FSC1N001

Model Number: CSN-S02A8-03000-3TL6A-S Category: Facility Side Cable Sub Category: Standard Power Configuration: 30A, 208V, 4.9kW

#### **Product Summary:**

Facility Side Cable, 30A, 208V, 4.9kW, 10ft / 3m power cord with L6-30P with Universal Connector.

## **Plug Form:**



L6-30P

## **Product Specification and Options**

### **System Features**

Compatibility	For use with Vertiv Geist Universal Rack PDU (UPDU)
Voltage	200-240V
Current	30A

Vertiv.com | Vertiv Headquarters, 505 N. Cleveland Avenue, Westerville, OH, 43082, USA

© Vertix Group Corp. All rights reserved. Vertix<sup>™</sup>, and the Vertix log are trademarks or registered trademarks of Vertix Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertix Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertix's sole discretion upon notice.

Frequency	50/60Hz
Power Cable Wire Gauge	10/3
Power Cable Length	10ft / 3m
Plug Type	NEMA L6-30P Twistlock
Max Plug kW	4.9kW (208V)
Output Connector	Universal Connector
UPDU Voltage per Receptacle/Socket	208-240V
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	UL & c-UL Listed 62368-1
Certification/Agency Approvals	RoHS Compliant
Shipped Weight	3lbs (1.36kg)

Vertiv.com | Vertiv Headquarters, 505 N. Cleveland Avenue, Westerville, OH, 43082, USA © Vertiv Group Corp. All rights reserved. Vertiv ", and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here. Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.