

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G1009

Model Number: MG00XMRO-10C133-2C20A9C00-S

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 17in / 432mm, Horizontal/Vertical

Product Summary: rPDU, Basic Standard, 16A, 230V, 3.6kW, Horizontal/Vertical, (10) IEC C13, C20, Black Powder Coat.

Plug Form:



C20

Receptacle:



IEC C13
(Quantity: 10)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|------------------------------|--------------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 16A |
| VA per Input (Load Capacity) | 3.6kW (230V) |

| | |
|---|---|
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | No |
| Plug Type | IEC60320 C20 Power Inlet (cord sold separately) |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 10 |
| - Style | 1 Bank of 4; 1 Bank of 6 |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | Zero U or 1U |
| 19in Panel Mount Brackets | Yes |
| SLB-4 Brackets | Yes |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | C _p Mark |
| Certification/Agency Approvals | RCM Mark (EMC Only) |
| Chassis Dimensions (HxWxD) | 44mm x 432mm x 47mm |
| Shipped Weight | 2lbs (0.91kg) |