

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G1013

**Model Number:** MGOXAR0-16C133-2C20A9H00-S

**Category:** Metered

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Metered Standard, 16A, 230V, 3.6kW, Horizontal, (16) IEC C13, C20, Black Powder Coat.

**Monitoring:** Power - Local (A, V, W, PF)  
Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



C20

### Receptacle:



IEC C13  
(Quantity: 16)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|   |   |
|---|---|
| <b>Monitoring</b>                             | Power - Local (A, V, W, PF)<br>Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input |
| <b>Monitoring Level 1</b>                     | Aggregate - Total Unit Monitoring   |
| <b>Quantity Of Inputs</b>                     | 1   |
| <b>Voltage</b>                                | 200-240V  |
| <b>Current</b>                                | 16A   |
| <b>VA per Input (Load Capacity)</b>           | 3.6kW (230V)  |
| <b>Frequency</b>                              | 50/60Hz   |
| <b>Over Current Protection</b>                | None  |
| <b>Switch</b>                                 | No  |
| <b>Plug Type</b>                              | IEC60320 C20 Power Inlet (cord sold separately)   |
| <b>Receptacle/Socket Type #1</b>              | IEC C13   |
| <b>- Quantity on Face</b>                     | 4   |
| <b>- Quantity on Rear</b>                     | 12  |
| <b>- Style</b>                                | 1 Bank of 4; 2 Banks of 6   |
| <b>- Maximum Output per Receptacle/Socket</b> | 10A per receptacle bank   |
| <b>- Voltage per Receptacle/Socket</b>        | 230V  |
| <b>Maximum Operating Temperature</b>          | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>       | Black   |
| <b>Configuration</b>                          | 1U  |
| <b>Adjustable Mount Brackets</b>              | Yes   |
| <b>Product Warranty</b>                       | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years             |
| <b>Certification/Agency Approvals</b>         | CE Marked   |
| <b>Certification/Agency Approvals</b>         | UKCA Marked   |
| <b>Certification/Agency Approvals</b>         | Complies with IEC 62368-1 (DOC Available)   |
| <b>Certification/Agency Approvals</b>         | Complies with EN 55032 and EN 55035   |
| <b>Certification/Agency Approvals</b>         | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>         | C <sub>p</sub> Mark   |
| <b>Certification/Agency Approvals</b>         | RCM Mark (EMC Only)   |
| <b>Chassis Dimensions (HxWxD)</b>             | 44mm x 432mm x 165mm  |
| <b>Shipped Weight</b>                         | 4lbs (1.81kg)   |