

OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G1013

Model Number: MGOXAR0-16C133-2C20A9H00-S

Category: Metered

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Metered Standard, 16A, 230V, 3.6kW, Horizontal, (16) IEC C13, C20, Black Powder Coat.

Monitoring: Power - Local (A, V, W, PF)
Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

Plug Form:



C20

Receptacle:



IEC C13
(Quantity: 16)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring	Power - Local (A, V, W, PF) Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
Monitoring Level 1	Aggregate - Total Unit Monitoring
Quantity Of Inputs	1
Voltage	200-240V
Current	16A
VA per Input (Load Capacity)	3.6kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Plug Type	IEC60320 C20 Power Inlet (cord sold separately)
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	4
- Quantity on Rear	12
- Style	1 Bank of 4; 2 Banks of 6
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U
Adjustable Mount Brackets	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C _p Mark
Certification/Agency Approvals	RCM Mark (EMC Only)
Chassis Dimensions (HxWxD)	44mm x 432mm x 165mm
Shipped Weight	4lbs (1.81kg)