

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G1014

**Model Number:** MG0CXER0-10C133-2C20A9C00-S

**Category:** Metered

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 17in / 432mm, Horizontal/Vertical

**Product Summary:** rPDU, Metered Standard, 16A, 230V, 3.6kW, Horizontal/Vertical, (10) IEC C13, C20, Black Powder Coat.

**Monitoring:** Power - Local (A, V, W, PF)  
Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



C20

### Receptacle:



IEC C13  
(Quantity: 10)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Monitoring	Power - Local (A, V, W, PF) Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
Monitoring Level 1	Aggregate - Total Unit Monitoring
Quantity Of Inputs	1
Voltage	200-240V
Current	16A
VA per Input (Load Capacity)	3.6kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Plug Type	IEC60320 C20 Power Inlet (cord sold separately)
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	10
- Style	1 Bank of 4; 1 Bank of 6
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U or 1U
19in Panel Mount Brackets	Yes
SLB-4 Brackets	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C <sub>p</sub> Mark
Certification/Agency Approvals	RCM Mark (EMC Only)
Chassis Dimensions (HxWxD)	44mm x 432mm x 47mm
Shipped Weight	2lbs (0.91kg)