

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2109

Model Number: MG0AXEA0-12UKR3-7UKA6A10-S

Category: Basic

Sub Category: Standard

Power Configuration: 13A, 230V, 2.9kW

Physical Configuration: 39in / 978mm, Vertical

Product Summary: rPDU, Basic Standard, 13A, 230V, 2.9kW, Vertical, (12) BS1363, 3m power cord with BS1363, Black Powder Coat.


Monitoring: Current - Local
Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

Plug Form:



BS1363

Receptacle:



BS1363
(Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring	Current - Local
	Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
Monitoring Level 1	Aggregate - Total Unit Monitoring
Quantity Of Inputs	1
Voltage	200-240V
Current	13A
VA per Input (Load Capacity)	2.9kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.5mm ² PVC
Power Cable Length	3m
Plug Type	BS 1363P
Receptacle/Socket Type #1	BS1363
- Quantity on Face	12
- Style	Individual - Right Hand Angled
- Maximum Output per Receptacle/Socket	13A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	39in / 978mm Vertical Rackmount
GE Vertical Mounting Bracket	Yes
Toolless Mounting Hardware - Center to Center Spacing	933.45mm
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C _μ Mark
Chassis Dimensions (LxWxD)	978mm x 54mm x 50mm
Shipped Weight	9lbs (4.08kg)