

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G2120

**Model Number:** MG00XEBO-20UKR3-3PS6B2A10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 66in / 1683mm, Vertical


**Product Summary:** rPDU, Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) BS1363, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



BS1363  
(Quantity: 20)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz

<b>Over Current Protection</b>	None
<b>Switch</b>	No
<b>Power Cable Wire Gauge</b>	4mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	3m
<b>Plug Type</b>	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
<b>Receptacle/Socket Type #1</b>	BS1363
<b>- Quantity on Face</b>	20
<b>- Style</b>	Individual - Right Hand Angled
<b>- Maximum Output per Receptacle/Socket</b>	13A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	66in / 1683mm Vertical Rackmount
<b>GE Vertical Mounting Bracket</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	1556mm and 1645mm
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	UKCA Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	C <sub>p</sub> Mark
<b>Chassis Dimensions (LxWxD)</b>	1683mm x 54mm x 50mm
<b>Shipped Weight</b>	14lbs (6.35kg)