

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G2192

**Model Number:** MG00XPR1-20C133-3PS6B2H10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 2U 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Standard, 32A, 230V, 7.3kW, Horizontal, (20) IEC C13, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 20)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Over Current Protection	(2) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	4mm <sup>2</sup> H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	20
- Quantity per Breaker	10
- Style	2 Banks of 4, 2 Banks of 6
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Flush Mount	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C <sub>p</sub> Mark
Certification/Agency Approvals	RCM Mark (EMC Only)
Chassis Dimensions (HxWxD)	88mm x 435mm x 100mm
Shipped Weight	11lbs (4.99kg)