

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G2195

**Model Number:** MG00XEB1-30C133-3PS6B2A10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Basic Standard, 32A, 230V, 7.3kW, Vertical, (30) IEC C13, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 30)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |              |
|------------------------------|--------------|
| Quantity Of Inputs           | 1            |
| Voltage                      | 200-240V     |
| Current                      | 32A          |
| VA per Input (Load Capacity) | 7.3kW (230V) |
| Frequency                    | 50/60Hz      |

|   |   |
|---|---|
| Over Current Protection                               | None  |
| Over Current Protection                               | (2) 16A Single Pole Magnetic Breakers   |
| Switch  | Breaker/Switch Combination  |
| Power Cable Wire Gauge                                | 4mm <sup>2</sup> H07RN-F  |
| Power Cable Length                                    | 3m  |
| Plug Type   | IEC60309 1P + N + E, 32A, 250V, Splashproof IP44  |
| Receptacle/Socket Type #1                             | IEC C13   |
| - Quantity on Face                                    | 30  |
| - Quantity per Breaker                                | 15  |
| - Style   | 2 Individual, 14 Banks of 2   |
| - Maximum Output per Receptacle/Socket                | 10A per receptacle bank   |
| - Voltage per Receptacle/Socket                       | 230V  |
| Maximum Operating Temperature                         | 60C / 140F  |
| Heavy Steel - Powder Coat Finish                      | Black   |
| Configuration   | 66in / 1683mm Vertical Rackmount  |
| GE Vertical Mounting Bracket                          | Yes   |
| Toolless Mounting Hardware - Center to Center Spacing | 1556mm and 1645mm   |
| Product Warranty                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals                        | CE Marked   |
| Certification/Agency Approvals                        | UKCA Marked   |
| Certification/Agency Approvals                        | Complies with IEC 62368-1 (DOC Available)   |
| Certification/Agency Approvals                        | Complies with EN 55032 and EN 55035   |
| Certification/Agency Approvals                        | RoHS Compliant  |
| Certification/Agency Approvals                        | C <sub>e</sub> Mark   |
| Certification/Agency Approvals                        | RCM Mark (EMC Only)   |
| Chassis Dimensions (LxWxD)                            | 1683mm x 50mm x 50mm  |
| Doghouse (D)  | 37mm  |
| Shipped Weight  | 13lbs (5.9kg)   |