

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G2199

**Model Number:** MG00XPRO-16IB43-2PS6B2H10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 2U 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Standard, 16A, 230V, 3.6kW, Horizontal, (12) IEC C13, (4) IEC C19, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 12)



IEC C19  
(Quantity: 4)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

## System Features

|   |   |
|---|---|
| Quantity Of Inputs                        | 1   |
| Voltage                                   | 200-240V  |
| Current                                   | 16A   |
| VA per Input (Load Capacity)              | 3.6kW (230V)  |
| Frequency                                 | 50/60Hz   |
| Over Current Protection                   | None  |
| Switch                                    | No  |
| Power Cable Wire Gauge                    | 2.5mm <sup>2</sup> H07RN-F  |
| Power Cable Length                        | 3m  |
| Plug Type                                 | IEC60309 1P + N + E, 16A, 250V, Splashproof IP44  |
| Combined Total Receptacle/Socket Quantity | 16  |
| Receptacle/Socket Type #1                 | IEC C13   |
| - Quantity on Face                        | 12  |
| - Style                                   | 2 Banks of 2, 2 Banks of 4  |
| - Maximum Output per Receptacle/Socket    | 10A per receptacle bank   |
| - Voltage per Receptacle/Socket           | 230V  |
| Receptacle/Socket Type #2                 | IEC C19   |
| - Quantity on Face                        | 4   |
| - Style                                   | Individual  |
| - Maximum Output per Receptacle/Socket    | 16A   |
| - Voltage per Receptacle/Socket           | 230V  |
| Maximum Operating Temperature             | 60C / 140F  |
| Heavy Steel - Powder Coat Finish          | Black   |
| Configuration                             | 19in / 483mm Horizontal Rackmount   |
| Flush Mount                               | Yes   |
| Product Warranty                          | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals            | CE Marked   |
| Certification/Agency Approvals            | UKCA Marked   |
| Certification/Agency Approvals            | Complies with IEC 62368-1 (DOC Available)   |
| Certification/Agency Approvals            | Complies with EN 55032 and EN 55035   |
| Certification/Agency Approvals            | RoHS Compliant  |
| Certification/Agency Approvals            | C <sub>p</sub> Mark   |
| Certification/Agency Approvals            | RCM Mark (EMC Only)   |
| Chassis Dimensions (HxWxD)                | 88mm x 435mm x 100mm  |
| Shipped Weight                            | 11lbs (4.99kg)  |