

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2201

Model Number: MG00X4A0-16IB43-2PS6B2A10-S

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 39in / 978mm, Vertical

Product Summary:

rPDU, Basic Standard, 16A, 230V, 3.6kW, Vertical, (12) IEC C13, (4) IEC C19, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Plug Form:



1P+N+E (IP44)

Receptacle:



IEC C13
(Quantity: 12)



IEC C19
(Quantity: 4)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--------------------|----------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 16A |

| | |
|--|---|
| VA per Input (Load Capacity) | 3.6kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | No |
| Power Cable Wire Gauge | 2.5mm ² H07RN-F |
| Power Cable Length | 3m |
| Plug Type | IEC60309 1P + N + E, 16A, 250V, Splashproof IP44 |
| Combined Total Receptacle/Socket Quantity | 16 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 12 |
| - Style | Banks of 4 |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank |
| - Voltage per Receptacle/Socket | 230V |
| Receptacle/Socket Type #2 | IEC C19 |
| - Quantity on Face | 4 |
| - Style | Individual |
| - Maximum Output per Receptacle/Socket | 16A |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 39in / 978mm Vertical Rackmount |
| GE Vertical Mounting Bracket | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 933.45mm |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | C _e Mark |
| Certification/Agency Approvals | RCM Mark (EMC Only) |
| Chassis Dimensions (LxWxD) | 978mm x 51mm x 51mm |
| Shipped Weight | 9lbs (4.08kg) |