

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.

## Part #: G2232

**Model Number:** MGOAXERO-12C133-2PS6B2H10-S

**Category:** Metered

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Metered Standard, 16A, 230V, 3.6kW, Horizontal, (12) IEC C13, 3m power cord with 1P+N+E (IP44), Black Powder Coat.


**Monitoring:** Current - Local  
Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 12)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                    |  |
|--------------------|--|
| Monitoring         | Current - Local  |
|                    | Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input |
| Monitoring Level 1 | Aggregate - Total Unit Monitoring  |

|  |   |
|--|---|
| Quantity Of Inputs                     | 1   |
| Voltage                                | 200-240V  |
| Current                                | 16A   |
| VA per Input (Load Capacity)           | 3.6kW (230V)  |
| Frequency                              | 50/60Hz   |
| Over Current Protection                | None  |
| Switch                                 | No  |
| Power Cable Wire Gauge                 | 2.5mmÂ² H07RN-F   |
| Power Cable Length                     | 3m  |
| Plug Type                              | IEC60309 1P + N + E, 16A, 250V, Splashproof IP44  |
| Receptacle/Socket Type #1              | IEC C13   |
| - Quantity on Face                     | 12  |
| - Style                                | Banks of 2  |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank   |
| - Voltage per Receptacle/Socket        | 230V  |
| Maximum Operating Temperature          | 60C / 140F  |
| Heavy Steel - Powder Coat Finish       | Black   |
| Configuration                          | 19in / 483mm Horizontal Rackmount   |
| Flush Mount                            | Yes   |
| Product Warranty                       | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals         | CE Marked   |
| Certification/Agency Approvals         | UKCA Marked   |
| Certification/Agency Approvals         | Complies with IEC 62368-1 (DOC Available)   |
| Certification/Agency Approvals         | Complies with EN 55032 and EN 55035   |
| Certification/Agency Approvals         | RoHS Compliant  |
| Certification/Agency Approvals         | RCM Mark (EMC Only)   |
| Certification/Agency Approvals         | C <sub>p</sub> Mark   |
| Chassis Dimensions (HxWxD)             | 44mm x 435mm x 100mm  |
| Shipped Weight                         | 4lbs (1.81kg)   |