

## OVERVIEW

Upgradeable Metered rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet while delivering a view of real-time view of power usage from a local LED display.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform metered rPDUs to monitored rPDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



## Part #: GI10052L

**Model Number:** MG01D1R1-10L133-3PS6C2H10-S

**Category:** Metered

**Sub Category:** Upgradeable

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Metered Upgradeable, 32A, 230V, 7.3kW, Horizontal, (10) Locking IEC C13, 3m power cord with 1P+N+E AU (IP66), Black Powder Coat.

### Monitoring:

Input and Breaker level current monitoring. Local high visibility LED display.

**Plug Form:**

1P+N+E AU (IP66)

**Receptacle:**Locking IEC C13  
(Quantity: 10)**Chassis Color Options:**

To discuss color options, contact your local sales representative.

**Product Specification and Options****System Features**

<b>Monitoring</b>	Input and Breaker level current monitoring. Local high visibility LED display.
<b>Monitoring Level 1</b>	Phase (A) Monitoring (kWh, W, VA, PF, V, A)  Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements
<b>Monitoring Level 2</b>	Circuit / Breaker Monitoring (A)  Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy
<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	200-240V
<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	7.3kW (230V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(2) 16A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Scrolling / Rotatable Digital Display</b>	Yes
<b>Power Cable Wire Gauge</b>	4mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	10ft / 3m
<b>Power Entry Location</b>	Left Rear
<b>Plug Type</b>	AS/NZS 3123 Industrial Plug, 1P + N + E, 32A, IP66 56P332
<b>Receptacle/Socket Type #1</b>	U-Lock IEC C13
<b>- Quantity on Rear</b>	10
<b>- Quantity per Breaker</b>	5
<b>- U-Lock Color ID</b>	2 Circuit = Orange, Green
<b>- Style</b>	Individual
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Internal RMS Voltage Sensor</b>	Yes
<b>Internal RMS Current Sensor</b>	Yes
<b>Maximum Operating Temperature</b>	60C / 140F

<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	1U
<b>Adjustable Mount Brackets</b>	Yes
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	UKCA Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	C <sub>p</sub> Mark
<b>Certification/Agency Approvals</b>	RCM Mark (EMC Only)
<b>Chassis Dimensions (HxWxD)</b>	44mm x 432mm x 216mm
<b>Shipped Weight</b>	14lbs (6.35kg)