

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: GI10094

Model Number: MG01X4W1-36CF13-3PS56B2A10-S-A

Category: Basic

Sub Category: Upgradeable

Power Configuration: 32A, 230/400V WYE, 22.0kW

Physical Configuration: 70in / 1778mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 32A, 230/400V WYE, 22.0kW, Vertical, (36) Combination C13/C19, 10ft power cord with 3P+N+E (IP44), Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



3P+N+E (IP44)

Receptacle:



Combination C13/C19
(Quantity: 36)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--------------------|---|
| Monitoring | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs | 1 |
| Voltage | 200-240/346-415V WYE |

| | |
|--|---|
| Current | 32A x 3 Phase WYE |
| VA per Input (Load Capacity) | 22.0kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | (6) 16A Single Pole Magnetic Breakers (10kAIC Rated) |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 6mm ² H07RN-F |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Bottom Front |
| Plug Type | IEC60309 3P + N + E, 32A, 230/400V, Splashproof IP44 |
| Alternating Phase/Circuits | Yes |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Face | 36 |
| - Quantity per Breaker | 6 |
| - Quantity per Phase | 12 |
| - Circuit Color ID | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | Zero U |
| 7938 Vertical Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in / 1556mm and 1645mm |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | RCM Mark (EMC Only) |
| Certification/Agency Approvals | China RoHS |
| Chassis Dimensions (LxWxD) | 70in x 2in x 2.25in / 1778mm x 51mm x 58mm |
| Shipped Weight | 19lbs (8.62kg) |