

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.

## Part #: I10001

**Model Number:** MN01X4B0-24D203-2ST5A0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 20A, 120V, 1.9kW, Vertical, (24) NEMA 5-20R, 10ft power cord with 5-20P, Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

### Plug Form:



5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 24)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Monitoring	No Monitoring (Upgradeable with IMD module)
Quantity Of Inputs	1
Voltage	100-120V
Current	20A
VA per Input (Load Capacity)	1.9kW (120V)
Frequency	50/60Hz

Over Current Protection	None
Switch	No
Power Cable Wire Gauge	12/3
Power Cable Length	10ft / 3m
Power Entry Location	Bottom Front
Plug Type	NEMA 5-20P
Receptacle/Socket Type #1	NEMA 5-20R
- Quantity on Face	24
- Style	Duplex
- Voltage per Receptacle/Socket	120V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	66in / 1683mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes
Toolless Mounting Hardware - Center to Center Spacing	61.25in and 64.75in
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	UL & c-UL Listed 62368-1
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Part 15 Class A Conformance
Chassis Dimensions (LxWxD)	66.25in x 2.0in x 2.0in
Shipped Weight	15lbs (6.8kg)