

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: I10004L

**Model Number:** MN01X4W1-36PT68-3PS6B0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 208V, 4.9kW

**Physical Configuration:** 72in / 1829mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 30A, 208V, 4.9kW, Vertical, (30) Locking IEC C13, (6) Locking IEC C19, 10ft power cord with 2P+E (IP44), Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

### Plug Form:



2P+E (IP44)

### Receptacle:



Locking IEC C13  
(Quantity: 30)



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

<b>Monitoring</b>	No Monitoring (Upgradeable with IMD module)
<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	200-240V
<b>Current</b>	30A
<b>VA per Input (Load Capacity)</b>	4.9kW (208V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(2) 20A Double Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	11/3 (4mm <sup>2</sup> )
<b>Power Cable Length</b>	10ft / 3m
<b>Power Entry Location</b>	Bottom Front
<b>Plug Type</b>	IEC60309 2P + E, 30A, Splashproof IP44
<b>Combined Total Receptacle/Socket Quantity</b>	36
<b>Receptacle/Socket Type #1</b>	U-Lock IEC C13
- Quantity on Face	30
- Quantity per Breaker	15
- U-Lock Color ID	2 Circuit = Orange, Green
- Style	Individual
- Voltage per Receptacle/Socket	208V
<b>Receptacle/Socket Type #2</b>	U-Lock IEC C19
- Quantity on Face	6
- Quantity per Breaker	3
- U-Lock Color ID	2 Circuit = Orange, Green
- Style	Individual
- Voltage per Receptacle/Socket	208V
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	72in / 1829mm Vertical Rackmount
<b>7938 Vertical Mounting Bracket Kit</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	61.25in and 64.75in
<b>Country of Origin</b>	USA, TAA Compliant and Buy American Act COTS Compliant
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	UL & c-UL Listed 62368-1
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Part 15 Class A Conformance
<b>Chassis Dimensions (LxWxD)</b>	72in x 2in x 2in
<b>Shipped Weight</b>	16lbs (7.26kg)