

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.

## Part #: I10013

**Model Number:** MN01X4B0-24D203-2TL5A0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Basic Upgradeable, 20A, 120V, 1.9kW, Vertical, (24) NEMA 5-20R, 10ft power cord with L5-20P, Black Powder Coat.

### Monitoring:

No Monitoring (Upgradeable with IMD module)

### Plug Form:



L5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 24)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |   |
|------------------------------|---|
| Monitoring                   | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs           | 1   |
| Voltage                      | 100-120V                                    |
| Current                      | 20A   |
| VA per Input (Load Capacity) | 1.9kW (120V)                                |
| Frequency                    | 50/60Hz                                     |

|  |   |
|--|---|
| <b>Over Current Protection</b>                               | None  |
| <b>Switch</b>  | No  |
| <b>Power Cable Wire Gauge</b>                                | 12/3  |
| <b>Power Cable Length</b>                                    | 10ft / 3m   |
| <b>Power Entry Location</b>                                  | Bottom Front  |
| <b>Plug Type</b>   | NEMA L5-20P Twistlock   |
| <b>Receptacle/Socket Type #1</b>                             | NEMA 5-20R  |
| <b>- Quantity on Face</b>                                    | 24  |
| <b>- Style</b>   | Duplex  |
| <b>- Voltage per Receptacle/Socket</b>                       | 120V  |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black   |
| <b>Configuration</b>   | 66in / 1683mm Vertical Rackmount  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in   |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant  |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 62368-1  |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | FCC Part 15 Class A Conformance   |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2.0in x 2.0in   |
| <b>Shipped Weight</b>  | 15lbs (6.8kg)   |