

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: I10037

**Model Number:** MN01X4W1-48C133-3PS56B0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 240/415V WYE, 17.2kW

**Physical Configuration:** 76in / 1930mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 30A, 240/415V WYE, 17.2kW, Vertical, (48) IEC C13, 10ft power cord with 3P+N+E (IP44), Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

**Plug Form:**



3P+N+E (IP44)

**Receptacle:**



IEC C13  
(Quantity: 48)

**Chassis Color Options:**



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

**Monitoring** No Monitoring (Upgradeable with IMD module)

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	200-240/346-415V WYE
<b>Current</b>	30A x 3 Phase WYE
<b>VA per Input (Load Capacity)</b>	17.2kW (240V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(6) 20A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	10/5
<b>Power Cable Length</b>	10ft / 3m
<b>Power Entry Location</b>	Bottom Front
<b>Plug Type</b>	IEC60309 3P + N + E, 30A, Splashproof IP44
<b>Receptacle/Socket Type #1</b>	IEC C13
<b>- Quantity on Face</b>	48
<b>- Quantity per Breaker</b>	8
<b>- Quantity per Phase</b>	16
<b>- Style</b>	Banks of 4
<b>- Voltage per Receptacle/Socket</b>	240V (L-N)
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	76in / 1930mm Vertical Rackmount
<b>7938 Vertical Mounting Bracket Kit</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	61.25in and 64.75in
<b>Country of Origin</b>	USA, TAA Compliant and Buy American Act COTS Compliant
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Part 15 Class A Conformance
<b>Certification/Agency Approvals</b>	UL & c-UL Listed 62368-1
<b>Chassis Dimensions (LxWxD)</b>	76in x 2in x 2.25in
<b>Shipped Weight</b>	19lbs (8.62kg)