

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: I10109L

**Model Number:** MN01X1R1-06L193-3PS56B0H10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 240/415V WYE, 17.2kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Basic Upgradeable, 30A, 240/415V WYE, 17.2kW, Horizontal, (6) Locking IEC C19, 10ft power cord with 3P+N+E (IP44), Black Powder Coat.

### Monitoring:

No Monitoring (Upgradeable with IMD module)

### Plug Form:



3P+N+E (IP44)

### Receptacle:



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Monitoring	No Monitoring (Upgradeable with IMD module)
Quantity Of Inputs	1
Voltage	200-240/346-415V WYE
Current	30A x 3 Phase WYE
VA per Input (Load Capacity)	17.2kW (240V)
Frequency	50/60Hz
Over Current Protection	(6) 20A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	10/5
Power Cable Length	10ft / 3m
Power Entry Location	Left Rear
Plug Type	IEC60309 3P + N + E, 30A, Splashproof IP44
Receptacle/Socket Type #1	U-Lock IEC C19
- Quantity on Rear	6
- Quantity per Breaker	1
- Quantity per Phase	2
- U-Lock Color ID	6 Circuit = Orange, Light Orange, Green, Light Green, Blue, Light Blue
- Style	Individual
- Voltage per Receptacle/Socket	240V (L-N)
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U
Adjustable Mount Brackets	Yes
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	UL & c-UL Listed 62368-1
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Part 15 Class A Conformance
Chassis Dimensions (HxWxD)	1.72in x 17in x 8.5in
Shipped Weight	15lbs (6.8kg)