

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: I10109L

Model Number: MN01X1R1-06L193-3PS56B0H10-S

Category: Basic

Sub Category: Upgradeable

Power Configuration: 30A, 240/415V WYE, 17.2kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Basic Upgradeable, 30A, 240/415V WYE, 17.2kW, Horizontal, (6) Locking IEC C19, 10ft power cord with 3P+N+E (IP44), Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



3P+N+E (IP44)

Receptacle:



Locking IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|----------------------------------|---|
| Monitoring | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs | 1 |
| Voltage | 200-240/346-415V WYE |
| Current | 30A x 3 Phase WYE |
| VA per Input (Load Capacity) | 17.2kW (240V) |
| Frequency | 50/60Hz |
| Over Current Protection | (6) 20A Single Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 10/5 |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Left Rear |
| Plug Type | IEC60309 3P + N + E, 30A, Splashproof IP44 |
| Receptacle/Socket Type #1 | U-Lock IEC C19 |
| - Quantity on Rear | 6 |
| - Quantity per Breaker | 1 |
| - Quantity per Phase | 2 |
| - U-Lock Color ID | 6 Circuit = Orange, Light Orange, Green, Light Green, Blue, Light Blue |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 240V (L-N) |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 1U |
| Adjustable Mount Brackets | Yes |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | FCC Part 15 Class A Conformance |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Chassis Dimensions (HxWxD) | 1.72in x 17in x 8.5in |
| Shipped Weight | 15lbs (6.8kg) |