

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: I10401

**Model Number:** MN01X4W1-36MR99-3TL14A0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 120/208V, 5.7kW

**Physical Configuration:** 70in / 1778mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 30A, 120/208V, 5.7kW, Vertical, (20) IEC C13, (4) IEC C19, (12) NEMA 5-20R, 10ft power cord with L14-30P, Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

**Plug Form:**

L14-30P

**Receptacle:**IEC C13  
(Quantity: 20)IEC C19  
(Quantity: 4)NEMA 5-20R  
(Quantity: 12)**Chassis Color Options:**

To discuss color options, contact your local sales representative.

**Product Specification and Options****System Features**

Monitoring	No Monitoring (Upgradeable with IMD module)
Quantity Of Inputs	1
Voltage	100-120/200-240V
Current	30A
VA per Input (Load Capacity)	5.7kW (208V)
Frequency	50/60Hz
Over Current Protection	(2) 20A Double Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	10/4
Power Cable Length	10ft / 3m
Power Entry Location	Bottom Front
Plug Type	NEMA L14-30P Twistlock
Combined Total Receptacle/Socket Quantity	36
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	20
- Quantity per Breaker	10
- Style	Banks of 5
- Voltage per Receptacle/Socket	208V
Receptacle/Socket Type #2	IEC C19
- Quantity on Face	4
- Quantity per Breaker	2
- Style	Individual
- Voltage per Receptacle/Socket	208V
Receptacle/Socket Type #3	NEMA 5-20R
- Quantity on Face	12
- Quantity per Breaker	6
- Style	Duplex
- Voltage per Receptacle/Socket	120V

<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	70in / 1778mm Vertical Rackmount
<b>7938 Vertical Mounting Bracket Kit</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	61.25in and 64.75in
<b>Country of Origin</b>	USA, TAA Compliant and Buy American Act COTS Compliant
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Part 15 Class A Conformance
<b>Certification/Agency Approvals</b>	UL & c-UL Listed 62368-1
<b>Chassis Dimensions (LxWxD)</b>	70in x 2in x 2in
<b>Shipped Weight</b>	17lbs (7.71kg)