

## OVERVIEW

Upgradeable Switched Outlet Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of outlet level power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. With the Geist Upgradeable hot-swap technology, users may easily update the rPDU technology with the addition of the appropriate Interchangeable Monitoring Device (IMD) as business needs change.

### Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote outlet-level power monitoring options offer quick access to critical power usage information down to the device level to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.



## Part #: NU30021

**Model Number:** MNU3EGB1-24S203-3TL5A0A10-S

**Category:** Switched

**Sub Category:** Outlet Level Monitoring

**Power Configuration:** 30A, 120V, 2.8kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Switched Outlet Level Monitoring EC, 30A, 120V, 2.8kW, Vertical, (24) NEMA 5-20R, 10ft / 3m power cord with L5-30P, Black Powder Coat.

**Monitoring:** Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display.

### Plug Form:



L5-30P

### Receptacle:



NEMA 5-20R  
(Quantity: 24)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

- Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices.

## Product Specification and Options

### System Features

|  |  |
|--|--|
| <b>Monitoring</b>                            | Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display. |
| <b>Input Monitoring</b>                      | Phase (A) Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements   |
| <b>Circuit Monitoring</b>                    | Circuit / Breaker Monitoring (A)<br><br>Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy  |
| <b>Outlet Monitoring</b>                     | Outlet Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements.   |
| <b>Remote Power Management</b>               | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up   |
| <b>Quantity Of Inputs</b>                    | 1  |
| <b>Voltage</b>                               | 100-120V   |
| <b>Current</b>                               | 30A  |
| <b>VA per Input (Load Capacity)</b>          | 2.8kW (120V)   |
| <b>Frequency</b>                             | 50/60Hz  |
| <b>Over Current Protection</b>               | (2) 20A Single Pole Magnetic Breakers (10kAIC Rated)   |
| <b>Switch</b>                                | Breaker/Switch Combination   |
| <b>Scrolling / Rotatable Digital Display</b> | Yes  |
| <b>Indicators - LED(s)</b>                   | 24   |
| <b>Power Cable Wire Gauge</b>                | 10/3   |
| <b>Power Cable Length</b>                    | 10ft / 3m  |
| <b>Power Entry Location</b>                  | Bottom Front   |
| <b>Plug Type</b>                             | NEMA L5-30P Twistlock  |
| <b>Receptacle/Socket Type #1</b>             | NEMA 5-20R   |
| <b>- Quantity on Face</b>                    | 24   |
| <b>- Quantity per Breaker</b>                | 12   |
| <b>- Style</b>                               | Individual   |
| <b>- Voltage per Receptacle/Socket</b>       | 120V   |
| <b>Network Connection</b>                    | Dual 10/100/1000Mbps Ethernet  |
| <b>Protocols Supported</b>                   | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP   |
| <b>Data Access Formats</b>                   | CSV datalog, JSON API, JSON datalog  |
| <b>USB Support</b>                           | Yes  |
| <b>IP Reset Button</b>                       | Yes  |
| <b>Hard Reboot Button</b>                    | Yes  |
| <b>Serial Connection</b>                     | RS232 via RJ45   |
| <b>Remote Sensor RJ Connection Jacks</b>     | 1 (Supports up to 16 Sensors)  |

|  |   |
|--|---|
| <b>Maximum Operating Temperature</b>                         | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black   |
| <b>Configuration</b>   | Zero U  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm   |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant  |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | FCC Part 15 Class A Conformance   |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 62368-1  |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2in x 2.6in / 1683mm x 51mm x 66mm  |
| <b>Shipped Weight</b>  | 20lbs (9.07kg)  |