

OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.

Part #: P1025

Model Number: PVHVRCN102-102182JS6

Category: Metered

Sub Category: Standard

Power Configuration: 20A, 200V, 4.0kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Metered Standard, 20A, 200V, 4.0kW, Horizontal, (8) IEC C13, (2) IEC C19, 3m power cord with 6-20P, Black Powder Coat.

Monitoring: Power - Local (A, V, W, PF)
Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

Plug Form:



6-20P

Receptacle:



IEC C13
(Quantity: 8)



IEC C19
(Quantity: 2)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring	Power - Local (A, V, W, PF) Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
Monitoring Level 1	Aggregate - Total Unit Monitoring
Quantity Of Inputs	1

Voltage	200-240V
Current	20A
VA per Input (Load Capacity)	4.0kW (200V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	3.5mm ²
Power Cable Length	3m
Plug Type	JIS C8303, 2P/3W, 20A, 250V, NEMA 6-20P
Combined Total Receptacle/Socket Quantity	10
Receptacle/Socket Type #1	IEC C13
- Quantity on Rear	8
- Style	Banks of 4
- Maximum Output per Receptacle/Socket	15A per receptacle bank
- Voltage per Receptacle/Socket	200V
Receptacle/Socket Type #2	IEC C19
- Quantity on Rear	2
- Style	Individual
- Maximum Output per Receptacle/Socket	20A
- Voltage per Receptacle/Socket	200V
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U
Adjustable Mount Brackets	Yes
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	METI DENAN
Chassis Dimensions (HxWxD)	44mm x 432mm x 165mm
Shipped Weight	7lbs (3.18kg)