

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: PI10001

Model Number: MP01X4W1-42IZ68-3JL6A5A10-S

Category: Basic

Sub Category: Upgradeable

Power Configuration: 30A, 200V, 6.0kW

Physical Configuration: 70in / 1778mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 30A, 200V, 6.0kW, Vertical, (36) IEC C13, (6) IEC C19, 3m power cord with L6-30P, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



L6-30P

Receptacle:



IEC C13
(Quantity: 36)



IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring No Monitoring (Upgradeable with IMD module)

| | |
|--|---|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 30A |
| VA per Input (Load Capacity) | 6.0kW (200V) |
| Frequency | 50/60Hz |
| Over Current Protection | (2) 20A Double Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 5.5mm ² |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Bottom Front |
| Plug Type | JIS C8303, 2P/3W, 30A, 250V Locking, NEMA L6-30P |
| Combined Total Receptacle/Socket Quantity | 42 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 36 |
| - Quantity per Breaker | 18 |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | 200V |
| Receptacle/Socket Type #2 | IEC C19 |
| - Quantity on Face | 6 |
| - Quantity per Breaker | 3 |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 200V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 70in / 1778mm Vertical Rackmount |
| 7938 Vertical Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 1556mm and 1645mm |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | METI DENAN |
| Chassis Dimensions (LxWxD) | 1778mm x 51mm x 51mm |
| Shipped Weight | 16lbs (7.26kg) |