

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: PI10014L

Model Number: MP01X4W0-42PZ67-2C20A9A00-S

Category: Basic

Sub Category: Upgradeable

Power Configuration: 20A, 100V or 200V, 2.0 or 4.0kW

Physical Configuration: 72in / 1829mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 20A, 100V or 200V, 2.0 or 4.0kW, Vertical, (36) Locking IEC C13, (6) Locking IEC C19, C20, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



C20

Receptacle:



Locking IEC C13
(Quantity: 36)



Locking IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring

No Monitoring (Upgradeable with IMD module)

Quantity Of Inputs	1
Voltage	100-240V
Current	20A
VA per Input (Load Capacity)	2.0kW (100V) or 4.0kW (200V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Entry Location	Bottom Front
Plug Type	IEC60320 C20 Power Inlet (cord sold separately)
Combined Total Receptacle/Socket Quantity	42
Receptacle/Socket Type #1	U-Lock IEC C13
- Quantity on Face	36
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100V or 200V
Receptacle/Socket Type #2	U-Lock IEC C19
- Quantity on Face	6
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100V or 200V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	72in / 1829mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes
Toolless Mounting Hardware - Center to Center Spacing	1556mm and 1645mm
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	METI DENAN
Chassis Dimensions (LxWxD)	1829mm x 51mm x 51mm
Shipped Weight	16lbs (7.26kg)