

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: UI10028

Model Number: DU01X4B1-30CF17-2S02A9K00-S-A

Category: Basic

Sub Category: Upgradeable

Power Configuration: Variable, Variable, 22.0kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 22.0kW, Variable Power Configuration, Vertical, (30) Combination C13/C19, Universal Inlet, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



Universal Inlet

Receptacle:



Combination C13/C19
(Quantity: 30)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|---|--|
| Monitoring | No Monitoring (Upgradeable with IMD module) |
| Maximum Input Power (Defined by Facility Side Cable) | 63A Single Phase, 240V Max, 14.4kW 48A 3 Phase DELTA, 240V Max, 19.9kW 32A Three Phase WYE, 240/415V Max, 22.0kW |

| | |
|--|---|
| Frequency | 50/60Hz |
| Over Current Protection | (6) 16A Double Pole Magnetic Breakers (10kAIC Rated) |
| Switch | Breaker/Switch Combination |
| Power Entry Location | Pivoting Connector |
| Plug Type | Universal Inlet |
| Alternating Phase/Circuits | Yes |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Face | 30 |
| - Quantity per Breaker | 5 |
| - Circuit Color ID | 6 Circuit = Orange, Light Orange, Green, Light Green, Blue, Light Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | Defined by Facility Side Cable |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | Zero U |
| 4689 UPDU Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 49in and 61.25in / 1245mm and 1556mm |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | FCC Part 15 Class A Conformance |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Chassis Dimensions (LxWxD) | 66.25in x 2in x 2.5in / 1682mm x 51mm x 64mm |
| Doghouse (D) | 1.4in / 36mm |
| Shipped Weight | 21lbs (9.53kg) |