


## OVERVIEW

Upgradeable Switched Unit Level Monitored EC rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of input power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. Upgrade the hot-swappable monitoring device on select units to leverage new technologies and accommodate changing business needs.

### Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce



## Part #: US30002L

**Model Number:** MUS3EGB0-24PK37-2C20A9A00-S

**Category:** Switched

**Sub Category:** Unit Level Monitoring

**Power Configuration:** 16A OR 20A, 120V OR 208V OR 230V, 1.9kW or 3.3kW or 3.6kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Switched Unit Level Monitoring EC, 16A OR 20A, 120V OR 208V OR 230V, 1.9kW or 3.3kW or 3.6kW, Vertical, (21) Locking IEC C13, (3) Locking IEC C19, C20, Black Powder Coat.

### Monitoring:

Input power monitoring with Outlet switching. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display.

### Plug Form:



C20

### Receptacle:



Locking IEC C13  
(Quantity: 21)



Locking IEC C19  
(Quantity: 3)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

deployment time with self-configuration of downstream devices.

## Product Specification and Options

### System Features

|  |   |
|--|---|
| <b>Monitoring</b>                                | Input power monitoring with Outlet switching. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display. |
| <b>Input Monitoring</b>                          | Phase (A) Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements                        |
| <b>Remote Power Management</b>                   | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up  |
| <b>Quantity Of Inputs</b>                        | 1   |
| <b>Voltage</b>                                   | 100-240V  |
| <b>Current</b>                                   | 16A or 20A  |
| <b>VA per Input (Load Capacity)</b>              | 1.9kW (120V), 3.3kW (208V), 3.6kW (230V)  |
| <b>Frequency</b>                                 | 50/60Hz   |
| <b>Over Current Protection</b>                   | None  |
| <b>Switch</b>                                    | No  |
| <b>Scrolling / Rotatable Digital Display</b>     | Yes   |
| <b>Indicators - LED(s)</b>                       | 24  |
| <b>Power Entry Location</b>                      | Bottom Front  |
| <b>Plug Type</b>                                 | IEC60320 C20 Power Inlet (cord sold separately)   |
| <b>Combined Total Receptacle/Socket Quantity</b> | 24  |
| <b>Receptacle/Socket Type #1</b>                 | U-Lock IEC C13  |
| - Quantity on Face                               | 21  |
| - U-Lock Color ID                                | 1 Circuit = Orange  |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                  | 100-240V  |
| <b>Receptacle/Socket Type #2</b>                 | U-Lock IEC C19  |
| - Quantity on Face                               | 3   |
| - U-Lock Color ID                                | 1 Circuit = Orange  |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                  | 100-240V  |
| <b>Network Connection</b>                        | Dual 10/100/1000Mbps Ethernet   |
| <b>Protocols Supported</b>                       | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP  |
| <b>Data Access Formats</b>                       | CSV datalog, JSON API, JSON datalog   |
| <b>USB Support</b>                               | Yes   |
| <b>IP Reset Button</b>                           | Yes   |
| <b>Hard Reboot Button</b>                        | Yes   |
| <b>Serial Connection</b>                         | RS232 via RJ45  |
| <b>Remote Sensor RJ Connection Jacks</b>         | 1 (Supports up to 16 Sensors)   |
| <b>Maximum Operating Temperature</b>             | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>          | Black   |

|  |   |
|--|---|
| <b>Configuration</b>   | Zero U  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm   |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | CE Marked   |
| <b>Certification/Agency Approvals</b>                        | UKCA Marked   |
| <b>Certification/Agency Approvals</b>                        | Complies with IEC 62368-1 (DOC Available)   |
| <b>Certification/Agency Approvals</b>                        | Complies with EN 55032 and EN 55035   |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | FCC Part 15 Class A Conformance   |
| <b>Certification/Agency Approvals</b>                        | C <sub>p</sub> Mark   |
| <b>Certification/Agency Approvals</b>                        | RCM Mark (EMC Only)   |
| <b>Certification/Agency Approvals</b>                        | China RoHS  |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 62368-1  |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2in x 2.6in / 1683mm x 51mm x 66mm  |
| <b>Shipped Weight</b>  | 18lbs (8.16kg)  |