

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.

## Part #: VPOG0101

**Model Number:** MG00X7R0-08SKZ3-1C14A6H10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 10A, 230V, 2.3kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Basic Standard, 10A, 230V, 2.3kW, Horizontal, (8) German Schuko, 3m power cord with C14, Black Powder Coat.

### Plug Form:



C14

### Receptacle:



German Schuko  
(Quantity: 8)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	10A
VA per Input (Load Capacity)	2.3kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.0mm <sup>2</sup> H05VVF

<b>Power Cable Length</b>	3m
<b>Plug Type</b>	IEC60320 C14 (corded)
<b>Receptacle/Socket Type #1</b>	German Schuko
<b>- Quantity on Face</b>	8
<b>- Style</b>	Individual
<b>- Maximum Output per Receptacle/Socket</b>	16A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	19in / 483mm Horizontal Rackmount
<b>Flush Mount</b>	Yes
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	UKCA Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Chassis Dimensions (HxWxD)</b>	67mm x 435mm x 60mm
<b>Shipped Weight</b>	4lbs (1.81kg)