

OVERVIEW

Upgradeable Unit Level EC Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering a comprehensive view of input level power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. Upgrade the hot-swappable monitoring device on select units to leverage new technologies and accommodate changing business needs.

Benefits

- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Every unit is 100% tested for reliability and functionality.
- Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices.



Part #: VP4G20AC

Model Number: MG05M4B0-30PN63-2PS56B2A10-S-A-RC

Category: Monitored

Sub Category: Unit Level

Power Configuration: 16A, 230/400V WYE, 11.0kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary:

rPDU, Monitored Unit Level EC, Residual Current Metering Type B, 16A, 230/400V WYE, 11.0kW, Vertical, (24) Locking IEC C13, (6) Locking IEC C19, 3m power cord with 3P+N+E (IP44), Black Powder Coat.

Monitoring:

Input and per Phase power monitoring with Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.

Plug Form:



3P+N+E (IP44)

Receptacle:



Locking IEC C13
(Quantity: 24)



Locking IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--|---|
| Monitoring | Input and per Phase power monitoring with Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display. |
| Monitoring Level 1 | Aggregate - Total Unit Monitoring (kWh, W, VA, PF) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements |
| Monitoring Level 2 | Phase (A, B, C) Monitoring (kWh, W, VA, PF, V, A) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements |
| Monitoring Level 3 | Circuit / Breaker Monitoring (A) Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy |
| Residual Current Metering (RCM) | Phase (A, B, C) Type B (AC/DC) with operating characteristics defined in IEC 62020:1998+AMD1:2003. |
| Quantity Of Inputs | 1 |
| Voltage | 200-240/346-415V WYE |
| Current | 16A x 3 Phase WYE |
| VA per Input (Load Capacity) | 11.0kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | No |
| LCD Touchscreen Display / Auto Oriented | Yes |
| Power Cable Wire Gauge | 2.5mm ² H07RN-F |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Bottom Front |
| Plug Type | IEC60309 3P + N + E, 16A, 230/400V, Splashproof IP44 |
| Combined Total Receptacle/Socket Quantity | 30 |
| Alternating Phase/Circuits | Yes |
| Receptacle/Socket Type #1 | U-Lock IEC C13 |
| - Quantity on Face | 24 |
| - Quantity per Phase | 8 |
| - U-Lock Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 230V |
| Receptacle/Socket Type #2 | U-Lock IEC C19 |
| - Quantity on Face | 6 |
| - Quantity per Phase | 2 |
| - U-Lock Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 230V |
| Internal RMS Voltage Sensor | Yes |
| Internal RMS Current Sensor | Yes |

| | |
|--|--|
| Network Connection | Dual 10/100/1000Mbps Ethernet |
| Protocols Supported | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP |
| Data Access Formats | CSV datalog, JSON API, JSON datalog |
| USB Support | Yes |
| IP Reset Button | Yes |
| Hard Reboot Button | Yes |
| Serial Connection | RS232 via RJ45 |
| Remote Sensor RJ Connection Jacks | 1 (Supports up to 4 Sensors) |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 66in / 1683mm Vertical Rackmount |
| 7938 Vertical Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 1556mm and 1645mm |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | C _p Mark |
| Chassis Dimensions (LxWxD) | 1683mm x 51mm x 51mm |
| Shipped Weight | 15lbs (6.8kg) |